

MEETS STANDARDS FOR



EN ISO:3059

SPECTROLINE®
NDT

EDGE™ 13 SERIES

LED UV-A Penetrant Station Flood Lamp

EDG-13T

Designed specifically for NDT professionals who require a rugged, high-intensity lamp to spot fluorescent indications on large parts. Perfect for use in automotive, fabrication, machining, oil/gas, and more industries!

**IP65
RATED**



**Dust Tight &
Water Resistant**



**NDT Inspection
Booths**



**Screening of
Fluorescent Particles**

FANLESS

Cool running design that uses state-of-the-art heat sinks

EASILY MOUNTABLE

For overhead inspection or in-line applications

FLEXIBLE ARM

For mounting at specific angles

GANGABLE

Can be ganged together to provide an even wider coverage area

13 UV-A LEDS

Provides large area of coverage for the largest, most even overhead beam available

LONG-LASTING UV-A LENSES

Virtually eliminate clouding/solarization



**CERTIFICATE OF
LIGHT OUTPUT**
included with lamp

EDGE™ 13 EDG-13T

MODEL	NOMINAL STEADY-STATE UV-A (365 nm) INTENSITY at 15 in (38 cm) ①	VISIBLE LIGHT MEASUREMENT	UV-A COVERAGE AREA (at minimum 1,200 μW/cm²)
EDG-13T	6,500 μW/cm²	< 1 foot-candle (11 lux)	17 x 15 in (43 x 38 cm)

Light Source:	13 UV-A (365 nm) LEDs
Lamp Style:	Panel flood lamp
Length: (L x W x H)	11 x 14 x 9 in (28 x 36 x 23 cm)
Weight:	14 lb (6.4 kg)
Power Requirements:	AC power (main AC power cord supplied with the unit) (Available in 100-120V, 230V and 240V versions)



CERTIFICATE OF LIGHT OUTPUT

① UV-A intensity reading taken with the Spectroline® AccuMAX™ Series meter, and are factory set to the values shown.

For applications requiring extremely large coverage area, the EDGE™ 13 can be quickly ganged together.



*Optional accessory: ganged cables with connectors (130156)

UV-A Beam Profiles

